



These machines were developed with specific goal, to be the best floor saw for the most demanding working conditions, the environment of rental shops.





TYPE	Dimensions (mm)				
RZ 200	HMIN	HMAX	W	DMIN	DMAX
	950	1250	540	500	520

TECHNICAL PARAMETERS

OPERATING PARAMETERS

Weight	[kg]	110
Maximal cutting depth	[mm]	190/200
Blade diameter	[mm]	500 (520)
Blade connection	[mm]	25,4
Rpm w/o load	[rpm]	2500
Drive	[-]	Manual
Electric start	[-]	No

ENGINE

Maker and type	Honda	GX 390
Fuel	[-]	Petrol
Net power (3600 rpm)	[kW]	8,7
Cyclone filter	[-]	No
Emission class	[-]	EU Stage V

OPERATING FLUIDS

Water tank capacity (sprinkling)	[l]	20
Fuel tank capacity (petrol)	[l]	6,1
Engine oil capacity (10W/30)	[l]	1,1

HYGIENIC PARAMETERS

Noice level $L_{pA,d}$	[dB]	92
Noice level $L_{WA,G}$	[dB]	101+4
Vibration a_{hvd}	[m/s ²]	5,22+2,09

FEATURES

- Frame design
- Lifting eye
- Handbrake
- Integrated sprinkling system
- Sealed bearings in the wheels

OPTIONAL ACCESSORIES

- Hour counter ☐
- Trottle level on the control panel ☐
- Diamond blade for asphalt ☐
- Diamond blade for concrete and reinforced concrete ☐